



KZDO-M410 DIESEL GENERATOR SET / 50Hz

OUTPUT RATINGS	50 Hz / 400V
Standby Power	410 kVA
	328 KW
Prime Power	375 kVA
	300 KW

ENGINE (ESP -STAND-BY)	
Manufacturer	DOOSAN
Origin	SOUTH KOREA
Model	P158LE-1
No of Cylinder / Configuration	8 / V TYPE
Displacement (lt)	14,60
Bore / Stroke (mm)	128 / 142
Cycle	4
Compression Ratio	15.00 :1
Aspiration	Turbocharged
Governor Type	Electronic
Cooling System	Water
Coolant Capacity (lt)	88,5
Lubrication Oil Capacity (lt)	21
Injection	Direct
Speed / Frequency	1500 / 50 Hz
Engine Power (kWm)	362
Fuel Consumption (l/h)	100% 78,7
	50% 40



Sound Proof Canopy

Special design for minimizing acoustic level
Galvanised steel construction further protected by polyester powdercoat paint
Black finish stainless steel locks and hinges
Control panel viewing window in a lockable access door
Emergency stop push button (red) mounted on enclosure exterior
Lifting, drag and jacking points on base frame
Radiato fill via removable, flush mounted rain cap fitted with compression seal
Acoustic insulation with moisture-repellent and non-flammable material

Emergency Standby Power (ESP)

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Prime Power

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3)



ALTERNATOR

Manufacturer	MECC ALTE
Origin	ITALY
Model	ECO 40-1S/4
No of Phase	3
Power Factor	cos 0,8
Number of Bearing	SINGLE
No of Poles	4
No of Leads	12
Voltage Regulation (SteadyState)	± %1
Insulation Class	H
Degree of Protection	IP 22/23
Excitation System	AVR, Brushless
Connection Type	Y Type
Total Harmonic Content (No Load)	< %3
Frequency (Hz)	50
Voltage Output (VAC)	230 / 400
Efficiency (%)	%93,9

Dimensions	WxLxH	Weight	Fuel Tank	Noise
	mm	kg	lt	db(A)
CANOPIED	1606x4460x2427	4024	700	
OPEN SET	1550x2965x1994	3030	700	

CONTROL UNIT

STANDART: Datakom309

OPTIONAL: Deepsea



KZ POWER reserves the right to amend details and specifications without notice.
Images for illustration purposes only. Generating set may include optional accessories.



KZ ENERJİ ÇÖZÜMLERİ ve DİŞ TİC. LTD. ŞTİ.
Mimar Sinan Mah. Bosna Caddesi No : 1/6
Cekmekoy / İstanbul / Turkey
T : +90 216 527 29 19
M : +90 532 255 76 77
F : +90 216 641 96 47
www.kzpower.com
info@kzpower.com