

## KZP-S400 DIESEL GENERATOR SET / 50Hz

OUTPUT RATINGS	50 Hz / 400V
Standby Power	400 kVA
	320 KW
Prime Power	350 kVA
	280 KW

ENGINE (ESP -STAND-BY)	
Manufacturer	PERKINS
Origin	UK
Model	2206A(C)E13TAG2
No of Cylinder / Configuration	6 / IN LINE
Displacement (lt)	13
Bore / Stroke (mm)	137 / 157
Cycle	4
Compression Ratio	16.3 :1
Aspiration	Turbo Aftercooler
Governor Type	Electronic
Cooling System	Water
Coolant Capacity (lt)	51,4
Lubrication Oil Capacity (lt)	40
Injection	Direct
Speed / Frequency	1500 / 50 Hz
Engine Gross Power (kWm)	305
Fuel Consumption (lt/h)	100% 71
	50% 37

### Emergency Standby Power (ESP)

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

### Prime Power

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3)



## ALTERNATOR

Manufacturer	STAMFORD
Origin	UK
Model	HC444E
No of Phase	3
Power Factor	cos 0,8
Number of Bearing	SINGLE
No of Poles	4
No of Leads	12
Voltage Regulation (Steady State)	± %1
Insulation Class	H
Degree of Protection	IP 21/23
Excitation System	AVR, Brushless
Connection Type	STAR
Total Harmonic Content (No Load)	< %2
Frequency (Hz)	50
Voltage Output (VAC)	230 / 400
Efficiency ( %)	%93,3

### Sound Proof Canopy



Special design for minimizing acoustic level  
Galvanised steel construction further protected by polyester powdercoat paint  
Black finish stainless steel locks and hinges  
Control panel viewing window in a lockable access door  
Emergency stop push button (red) mounted on enclosure exterior  
Lifting, drag and jacking points on base frame  
Radiato fill via removable, flush mounted rain cap fitted with compression seal  
Acoustic insulation with moisture-repellent and non-flammable material

Dimensions	WxLxH	Weight	Fuel Tank	Noise
	mm	kg	lt	db(A)
CANOPIED	1400x4810x2465	4020	1000	
OPEN SET	1370x3500x2090	2755	1000	

## CONTROL UNIT

### STANDART: Datakom309



### OPTIONAL: Deepsea

