



**3 PHASE INPUT  
MONO PHASE OUTPUT  
10 -30 kVA**

## **Application Areas**

Offices / Hospitals  
Power Plants  
Telecommunication  
Information Technologies  
Houses / Factories

[www.kzpower.com](http://www.kzpower.com)

MODEL	Mono Phase Input / Mono Phase Output 10 - 30 kVA
<b>INPUT</b>	
Number of Input Phase	3 Phase
Input Voltage Toleration	± % 10
Input Frequency	50 - 60 Hz
Input Power Factor	>98 %
<b>OUTPUT</b>	
Transfer Time	0 ms
Output Voltage	220 VAC
Output Wave Shape	Sine Wave
THD % Linear Load	< 3%, (not linear load: < 5%)
Efficiency	< % 92
<b>GENERAL</b>	
Working Heat	0/40°C
Protection Class	IP20
<b>BATTERY</b>	
Battery Type	Fully closed , dry type, maintenance-free
Battery Working Heat	< 25 °C
<b>PROTECTIONS</b>	
Protections	Short circuit, over heat, over load, high voltage, low battery level
<b>PHYSICAL FEATURE</b>	
Weight (kg)	30-50-70
<b>BATTERY</b>	
Security - EMC Standart	EN 62040-1-1 security / EN 62040-2 EMC
<b>COMMUNICATION</b>	
Interface Communication Portal	RS-232
Optional	Internal or external SNMP, dry contact card, USB card, external manual bypass

TECHNICAL FEATURES

DIMENSIONS			
POWER	G (mm)	D (mm)	H (mm)
10 - 15 kVA	325	500	500
15 - 20 kVA	325	600	600
20 - 30 kVA	325	700	700

