

KZP-6L1875 DIESEL GENERATOR SET / 60Hz



OUTPUT RATINGS

60 Hz / 480V

Standby Power	1875 kVA
	1500 KW
Prime Power	1710 kVA
	1368 KW

Emergency Standby Power (ESP)

These ratings are applicable for supplying continuous electrical power (at variable load). There is 200 operation hours/year limitation and this model can supply 10% overload power for 1 hour in 12 hours.

ENGINE (ESP -STAND-BY)

Manufacturer	PERKINS
Origin	UK
Model	4012-46TAG3A
No of Cylinder / Configuration	12 / V
Displacement (lt)	45,842
Bore / Stroke (mm)	160 / 190
Cycle	4
Compression Ratio	13,6:1
Aspiration	Turbo
Governor Type	Electronic
Cooling System	Water
Coolant Capacity (lt)	207
Lubrication Oil Capacity (lt)	177
Injection	Direct
Speed / Frequency	1800 / 60 Hz
Engine Gross Power (kWm)	1500
Fuel Consumption (lt/h)	100% 361
	50% 188

Prime Power

These ratings are applicable for supplying continuous electrical power (at variable load). No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3)

ALTERNATOR

Manufacturer	LEROY SOMER
Origin	FRANCE
Model	LSA 52.3 S5
No of Phase	3
Power Factor	cos 0,8
Number of Bearing	SINGLE
No of Poles	4
No of Leads	12
Voltage Regulation (Steady State)	± 0,5
Insulation Class	H
Degree of Protection	IP 21/23
Excitation System	AVR, Brushless
Connection Type	STAR
Total Harmonic Content (No Load)	< 2%
Frequency (Hz)	60
Voltage Output (VAC)	220 / 480
Efficiency (%)	90,2

Sound Proof Canopy



Special design for minimizing acoustic level
Galvanised steel construction further protected by polyester powdercoat paint
Black finish stainless steel locks and hinges
Control panel viewing window in a lockable access door
Emergency stop push button (red) mounted on enclosure exterior
Lifting, drag and jacking points on base frame
Radiato fill via removable, flush mounted rain cap fitted with compression seal
Acoustic insulation with moisture-repellent and non-flammable material

Dimensions	WxLxH	Weight	Fuel Tank	Noise
	mm	kg	lt	db(A)
CANOPIED	2430x9080x3220	19282	3000	
OPEN SET	2400x5500x2690	10698	3000	

CONTROL UNIT

STANDART: Datakom D300

OPTIONAL: Datakom D500



KZ POWER reserves the right to amend details and specifications without notice.
Images for illustration purposes only. Generating set may include optional accessories.



KZ ENERJİ ÇÖZÜMLERİ ve DİS TİC. LTD. STİ.
Mimar Sinan Mah. Bosna Caddesi No : 1/6
Cekmekoy / İstanbul / Turkey
T : +90 216 527 29 19
M : +90 532 255 76 77
F : +90 216 641 96 47
www.kzpower.com
info@kzpower.com