

KZP-6L269 DIESEL GENERATOR SET / 60Hz



OUTPUT RATINGS	60 Hz / 480V
Standby Power	269 kVA
	215 KW
Prime Power	245 kVA
	196 KW

Emergency Standby Power (ESP)

These ratings are applicable for supplying continuous electrical power (at variable load). There is 200 operation hours/year limitation and this model can supply 10% overload power for 1 hour in 12 hours.

ENGINE (ESP -STAND-BY)	
Manufacturer	PERKINS
Origin	UK
Model	1306A-E87TAG4
No of Cylinder / Configuration	6 / IN LINE
Displacement (lt)	8,7
Bore / Stroke (mm)	116 / 135
Cycle	4
Compression Ratio	16.9:1
Aspiration	Turbo
Governor Type	Electronic
Cooling System	Water
Coolant Capacity (lt)	24,2
Lubrication Oil Capacity (lt)	26,4
Injection	Direct
Speed / Frequency	1800 / 60 Hz
Engine Gross Power (kWm)	164
Fuel Consumption (lt/h)	100% 56
	50%34

Prime Power

These ratings are applicable for supplying continuous electrical power (at variable load). No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3)

ALTERNATOR

Manufacturer	LEROY SOMER
Origin	FRANCE
Model	LSA 46.2 L6
No of Phase	3
Power Factor	cos 0,8
Number of Bearing	SINGLE
No of Poles	4
No of Leads	12
Voltage Regulation (Steady State)	± 0,5
Insulation Class	H
Degree of Protection	IP 21/23
Excitation System	AVR, Brushless
Connection Type	STAR
Total Harmonic Content (No Load)	< %2
Frequency (Hz)	60
Voltage Output (VAC)	220 / 480
Efficiency (%)	%90,2

Sound Proof Canopy



Special design for minimizing acoustic level
Galvanised steel construction further protected by polyester powdercoat paint
Black finish stainless steel locks and hinges
Control panel viewing window in a lockable access door
Emergency stop push button (red) mounted on enclosure exterior
Lifting, drag and jacking points on base frame
Radiato fill via removable, flush mounted rain cap fitted with compression seal
Acoustic insulation with moisture-repellent and non-flammable material

Dimensions	WxLxH	Weight	Fuel Tank	Noise
	mm	kg	lt	db(A)
CANOPIED	1500x2800x2580	3100	400	
OPEN SET	1500x2800x1720	2113	400	

CONTROL UNIT

STANDART: Datakom D300



OPTIONAL: Datakom D500

