

## KZP-6L375 DIESEL GENERATOR SET / 60Hz



### OUTPUT RATINGS

60 Hz / 480V

Standby Power	375 kVA
	300 KW
Prime Power	338 kVA
	270 KW

### Emergency Standby Power (ESP)

These ratings are applicable for supplying continuous electrical power (at variable load). There is 200 operation hours/year limitation and this model can supply 10% overload power for 1 hour in 12 hours.

### Prime Power

These ratings are applicable for supplying continuous electrical power (at variable load). No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3)

### ENGINE (ESP -STAND-BY)

Manufacturer	PERKINS
Origin	UK
Model	1506A-E88TAG4
No of Cylinder / Configuration	6 / IN LINE
Displacement (lt)	8,8
Bore / Stroke (mm)	112 / 149
Cycle	4
Compression Ratio	16.1:1
Aspiration	Turbo
Governor Type	Electronic
Cooling System	Water
Coolant Capacity (lt)	29,6
Lubrication Oil Capacity (lt)	41
Injection	Direct
Speed / Frequency	1800 / 60 Hz
Engine Gross Power (kWm)	278
Fuel Consumption (lt/h)	100% 68
	50% 36

### ALTERNATOR

Manufacturer	LEROY SOMER
Origin	FRANCE
Model	LSA 46.2 L9
No of Phase	3
Power Factor	cos 0,8
Number of Bearing	SINGLE
No of Poles	4
No of Leads	12
Voltage Regulation (Steady State)	± 0,5
Insulation Class	H
Degree of Protection	IP 21/23
Excitation System	AVR, Brushless
Connection Type	STAR
Total Harmonic Content (No Load)	< 2%
Frequency (Hz)	60
Voltage Output (VAC)	220 / 480
Efficiency (%)	90,2



### Sound Proof Canopy

Special design for minimizing acoustic level  
Galvanised steel construction further protected by polyester powdercoat paint  
Black finish stainless steel locks and hinges  
Control panel viewing window in a lockable access door  
Emergency stop push button (red) mounted on enclosure exterior  
Lifting, drag and jacking points on base frame  
Radiato fill via removable, flush mounted rain cap fitted with compression seal  
Acoustic insulation with moisture-repellent and non-flammable material

Dimensions	WxLxH	Weight	Fuel Tank	Noise
	mm	kg	lt	db(A)
CANOPIED	1500x4200x2580	4004	500	
OPEN SET	1500x3100x1960	2900	500	

### CONTROL UNIT

STANDART: Datakom D300

OPTIONAL: Datakom D500



KZ POWER reserves the right to amend details and specifications without notice.  
Images for illustration purposes only. Generating set may include optional accessories.



**KZ ENERJİ ÇÖZÜMLERİ ve DİS TİC. LTD. STİ.**  
Mimar Sinan Mah. Bosna Caddesi No : 1/6  
Cekmekoy / İstanbul / Turkey  
T : +90 216 527 29 19  
M : +90 532 255 76 77  
F : +90 216 641 96 47  
www.kzpower.com  
info@kzpower.com