

## KZP-6S17 DIESEL GENERATOR SET / 60Hz



OUTPUT RATINGS	60 Hz / 480V
Standby Power	17 kVA
	13,6 KW
Prime Power	16 kVA
	12,8 KW

### Emergency Standby Power (ESP)

These ratings are applicable for supplying continuous electrical power (at variable load). There is 200 operation hours/year limitation and this model can supply 10% overload power for 1 hour in 12 hours.

ENGINE (ESP -STAND-BY)	
Manufacturer	PERKINS
Origin	UK
Model	403D-15G
No of Cylinder / Configuration	3 / IN LINE
Displacement (lt)	1,496
Bore / Stroke (mm)	84 / 90
Cycle	4
Compression Ratio	22.5:1
Aspiration	Natural
Governor Type	Mechanical
Cooling System	Water
Coolant Capacity (lt)	6
Lubrication Oil Capacity (lt)	6
Injection	Direct
Speed / Frequency	1800 / 60 Hz
Engine Gross Power (kWm)	14,7
Fuel Consumption (g/kWh)	100% 249
	50% 275

### Prime Power

These ratings are applicable for supplying continuous electrical power (at variable load). No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3)

## ALTERNATOR

Manufacturer	STAMFORD
Origin	UK
Model	PIO44F
No of Phase	3
Power Factor	cos 0,8
Number of Bearing	SINGLE
No of Poles	4
No of Leads	12
Voltage Regulation (Steady State)	± %1
Insulation Class	H
Degree of Protection	IP 21/23
Excitation System	AVR, Brushless
Connection Type	STAR
Total Harmonic Content (No Load)	< %2
Frequency (Hz)	60
Voltage Output (VAC)	220 / 480
Efficiency (%)	%86,6

### Sound Proof Canopy



Special design for minimizing acoustic level  
Galvanised steel construction further protected by polyester powdercoat paint  
Black finish stainless steel locks and hinges  
Control panel viewing window in a lockable access door  
Emergency stop push button (red) mounted on enclosure exterior  
Lifting, drag and jacking points on base frame  
Radiato fill via removable, flush mounted rain cap fitted with compression seal  
Acoustic insulation with moisture-repellent and non-flammable material

Dimintions	WxLxH	Weight	Fuel Tank	Noise
	mm	kg	lt	db(A)
CANOPIED	745x2000x1400	770	140	
OPEN SET	750x1500x1100	520	140	

## CONTROL UNIT

### STANDART: Datakom D300



### OPTIONAL: Datakom D500

